

# VA703mb

**17" VALUE SERIES LCD**  
**WITH 8MS VIDEO RESPONSE**

## Reliable, high-quality performer.

ViewSonic's 17" VA703mb LCD is a high quality performer that fits in any budget. Fast ClearMotiv® 8ms video response, 300 nits of brightness (typ) and a 700:1 contrast ratio (typ) combine to deliver EXCELLENT FRONT-OF-SCREEN PERFORMANCE. The VA703mb delivers crystal-clear graphics and smooth, full-motion video in brilliant color. The OSD power lock secures your screen settings and the Kensington security port provides theft deterrence. With speakers integrated into the stylish, slim bezel, the VA703mb is AN EASY FIT WITH ANY OFFICE DÉCOR while saving valuable desktop real estate and providing a complete desktop experience. Home users, small office, education and government users will enjoy the VA703mb.



### HIGH STYLE. HIGH PERFORMANCE.

- > **Fast 8ms video response** delivers superior picture clarity
- > **Full 17" viewable screen**  
Displays a full, flat 17" viewable area with crisp detail and fully saturated color.
- > **1280x1024 native resolution**  
Incredible image detail for sharp text and graphics.
- > **High brightness and contrast**  
300-nit brightness (typ) and 700:1 contrast ratio (typ) for rich, detailed images.
- > **Multimedia enhanced**  
Save desk and workspace and enjoy rich, stereo sound with built-in stereo speakers.
- > **Stylish slim-bezel design**  
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **OSD/power lock secures your settings**  
Prevents changes to monitor settings and maintains an optimized image.
- > **OnView® controls for superior screen adjustability**  
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **Windows® Vista® approved**
- > **PC and Mac compatible**
- > **TCO '03 and ENERGY STAR® qualified**



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**  
See the difference® 

# VA703mb

17" VALUE SERIES LCD WITH 8MS VIDEO RESPONSE



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 ViewSonic Corporation. All rights reserved. [13845-01B-09/08] VA703mb-1

<b>LCD</b>	Type	17" color TFT active matrix SXGA LCD
	Display Area	13.3" horizontal x 10.6" vertical; 17.0" diagonal
	Optimum Resolution	1280x1024
	Contrast Ratio	700:1 (typ)
	Viewing Angles	160° horizontal, 160° vertical @ contrast ratio > 5:1
	Response Time	8ms (typ)
	Light Source	Long life 50,000 hrs (typ)
	Brightness	300 cd/m <sup>2</sup> (typ)
<b>VIDEO INPUT</b>	Panel Surface	Anti-glare
	Analog	RGB analog (75 ohms, 0.7 Vp-p)
	Frequency	F <sub>H</sub> : 30~82kHz, F <sub>V</sub> : 50~85Hz
<b>COMPATIBILITY</b>	Sync	H/V separated (TTL),
	PC	VGA up to 1280x1024 non-interlaced
<b>CONNECTOR</b>	Mac®*	Power Mac™ G3/G4/G5 up to 1280x1024
	Analog	15-pin mini D-sub
<b>POWER</b>	Power	3-pin AC plug (CEE22)
	Audio	Stereo mini jack
<b>AUDIO</b>	Speakers	2x1 watt
<b>POWER</b>	Voltage	AC 100~240V, (universal), 50~60Hz (auto switch)
	Consumption	35W (typ)
<b>CONTROLS</b>	Basic	Power, 1, down, up, 2
	OnView®	Auto image adjust, contrast, brightness, ViewMatch® color adjust (sRGB, 9300K, 6500K, 5400K, RGB), audio adjust (volume, mute), information (resolution, H. freq, V. freq, pixel clock, model number, serial number, web site), manual image adjust (H. size, H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
<b>OPERATING CONDITIONS</b>	Temperature	32~104°F (0~40°C)
	Humidity	10~90% (non-condensing)
<b>DIMENSIONS (W x H x D)</b>	Physical with stand	14.9" x 15.7" x 8.3" (379mm x 400mm x 210mm)
	Physical without stand	14.9" x 13.3" x 2.7" (379mm x 338mm x 68.5mm)
	Net with stand	8.6 lb. (3.9 kg)
	Net without stand	8.1 lb. (3.7 kg)
	Gross with stand	11.5 lb. (5.2 kg)
<b>REGULATIONS</b>	UL, cUL, FCC-B, CB, CE, NOM, GS, ERGO (covers ISO13406-2), TCO'03, BSMI, CCC, ENERGY STAR®, PSB, C-TICK, RoHS, WEEE	
<b>RECYCLE/DISPOSAL</b>	The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.	
<b>POWER MANAGEMENT</b>	Meets TCO'03 and ENERGY STAR® standards	
<b>PACKAGE CONTENTS</b>	LCD display, power cable, 15-pin VGA video cable, audio cable, Quick Start Guide, ViewSonic Wizard CD	
<b>WARRANTY</b>	Three-year limited warranty on parts, labor and backlight.	

**ViewSonic®**  
See the difference® 

For more product information, visit us on the web at ViewSonic.com